



TECHNICAL DATA

O RING	NBR-EPDM-VITON
SLIPPER	PTFE+CARBON FIBRE
FILTER	700 MICRON
NOZZLES POSITIONS	2-3-4
NOZZLES TYPE	MEG 1/8" NPT
MAX OPERATING FLOW	60 L/MIN
MIN OPERATING FLOW	15 L/MIN
MAX OPERATING PRESSURE	150 bar
MAX OPERATING TEMPERATURE	90° C
MIN PASS THROUGH HOLE	88 mm
MATERIAL	INOX + BRASS + ALUMINIUM
LUBRIFICANTS	NONE
CONICAL GEARS	FIXED Z=22 ROTATING Z=23
MODULE	2
COMPLETE CYCLE	23 ROTATIONS
COMPLETE CYCLE TIME	0.25 MIN (15 SEC) AT 90 RPM
ROTATION SPEED	90 TO 110 RPM
WEIGHT	3kg
BEVEL GEAR CLEANING	OPTION

VERSIONE	01	02	03	04	05
FOGLIO					
DATA					
VERSIONE	06	07	08	09	10
FOGLIO					
DATA					

NOTE:

DESCRIZIONE: SW053A
INSTALLATION DRAWING

Bolondi
CLEANING HEADS
MONTECCHIO E. (RE) - ITALY

DISEGN.: S.DL. CONTR.:
DATA: 29/01/2021 VERSIONE
SCALA
1:5 A3
CODICE: SW053A